



## Custom Oilfield Fluids / Drilling Fluids

Tiger Product	Oil Field Application	Composition and Density
Calcium Chloride (Liquid)	Drilling, completion, and workover fluids.	25% - 38% Ca/MgCl <sub>2</sub> with specific gravity ranging from 1.290 – 1.389 as required
Calcium Chloride / Calcium Nitrate Heavy Brines	Drilling, workover and completion fluids	CaCl <sub>2</sub> / Ca(NO <sub>3</sub> ) <sub>2</sub> with specific gravity ranging from 1.400-1.600 as required
Calcium Chloride / Calcium Nitrate Heavy Brines	Heavy density for use as drilling, workover and completion fluids	CaBr <sub>2</sub> , ZnBr <sub>2</sub> with specific gravity ranging from 1.700 – 2.300 as required
Calcium Nitrate	Drilling fluids	Ca(NO <sub>3</sub> ) <sub>2</sub> with specific gravity ranging from 1.200 – 1.600 as required
Potassium Chloride	Drilling, completion, and workover fluids	1% - 24% KCl with specific gravity ranging from 1.005 – 1.163 as required
Salt Brine Sodium Chloride	Drilling, completion, and workover fluids	20% NaCl/CaCl <sub>2</sub> with specific gravity of 1.200

- Ensured supply throughout the season
- Delivered by our dedicated transportation fleet
- Manufactured in Canada